

## TAG54L-788

Article Number: 594-54788

Laser Tag Label, 5.5" X 8.5", 2 Per Sheet, Polyester, White, 500/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG54L-788

**Type** TAG54L

**Color** White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Label, 5.5" X 8.5", 2 Per Sheet, Polyester, White, 500/pkg

### Product Dimensions

**Length L (Imperial)** 5.50 "

**Length L (Metric)** 139.7 mm

**Width W (Imperial)** 8.50 "

**Width W (Metric)** 215.9 mm

**Height H (Imperial)** 5.50 "

**Height H (Metric)** 139.7 mm

**Height of printable area (imperial)** 5.50 "

**Height of printable area (metric)** 139.7 mm

**Horizontal Repeat HR (imperial)** 8.500 "

**Horizontal Repeat HR (metric)** 215.90 mm

**Print Method** Laser

**Thickness T (Metric)** 64.0 µm

**Vertical Repeat VR (imperial)** 5.5 "

**Vertical Repeat VR (metric)** 139.70 mm

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 500

**Package Quantity (Metric)** 500

**Carton Quantity** 500 Pieces

Labels per Column 2

Labels per Row 1

Labels per Sheet 2

## Material and Specifications

---

**Material** Type 788, Polyethylenterephthalat (PET)

**Material Shortcut** 788

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +199°F (-40°C to +93°C)

**Operating Temperature** -40°F to +199°F (-40°C to +93°C)

**ROHS Compliant** Yes