

## TAG57L-788

Article Number: 594-57788

Laser Tag Label, 2.75" X 4.25", 8 Per Sheet, Polyester, White, 2000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG57L-788

**Type** TAG57L

**Color** White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Label, 2.75" X 4.25", 8 Per Sheet, Polyester, White, 2000/pkg

### Product Dimensions

**Length L (Imperial)** 2.75 "

**Length L (Metric)** 69.8 mm

**Width W (Imperial)** 4.25 "

**Width W (Metric)** 107.9 mm

**Height H (Imperial)** 2.75 "

**Height H (Metric)** 69.8 mm

**Height of printable area (imperial)** 2.75 "

**Height of printable area (metric)** 69.8 mm

**Horizontal Repeat HR (imperial)** 4.250 "

**Horizontal Repeat HR (metric)** 107.90 mm

**Print Method** Laser

**Thickness T (Metric)** 64.0 µm

**Vertical Repeat VR (metric)** 69.80 mm

**Vertical Repeat VR (imperial)** 2.75 "

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 2000

**Package Quantity (Metric)** 2000

**Carton Quantity** 2000 Pieces

Labels per Column 4

Labels per Row 2

Labels per Sheet 8

## Material and Specifications

---

**Material** Type 788, Polyethylenterephthalat (PET)

**Material Shortcut** 788

**Adhesive Shortcut** Acrylic

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +199°F (-40°C to +93°C)

**Operating Temperature** -40°F to +199°F (-40°C to +93°C)

**ROHS Compliant** Yes