

TAG66L-789

Article Number: 594-66789

Laser Tag Label, 3.6" X .375", 50 Per Sheet, Polyester, White, 1000/pkg



Download spec sheet

Base Data

Local Order Number TAG66L-789

Type TAG66L

Color White (WH)

Features and Benefits

- LaserTags are sheet fed for easy loading and fast printing.
- LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
- LaserTags are printable using toner for long term UV exposure.
- LaserTags come in a variety of label sizes and types to fit most applications.

Color Marking Field White (WH)

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Short Description Laser Tag Label, 3.6" X .375", 50 Per Sheet, Polyester, White, 1000/pkg

Product Dimensions

Length L (Imperial) 0.375 "

Length L (Metric) 9.52 mm

Width W (Imperial) 3.59 "

Width W (Metric) 91.4 mm

Height H (Imperial) 0.375 "

Height H (Metric) 9.52 mm

Height of printable area (imperial) 0.375 "

Height of printable area (metric) 9.52 mm

Horizontal Repeat HR (metric) 91.40 mm

Horizontal Repeat HR (imperial) 3.600 "

Print Method Laser

Thickness T (Metric) 35.0 µm

Vertical Repeat VR (imperial) 0.375 "

Vertical Repeat VR (metric) 9.52 mm

Width of Liner WL (metric) 215.00 mm

Width of Liner WL (imperial) 8.5 "

Logistics and Packaging

Quantity Per pack

Package Quantity	1000
Package Quantity (Metric)	1000
Carton Quantity	1000
Labels per Column	25
Labels per Row	2
Labels per Sheet	50

Material and Specifications

Material	Type 789, Polyethylenterephthalat (PET)
Material Shortcut	789
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
ROHS Compliant	Yes