

## TAG69L-789

Article Number: 594-69789

Laser Tag Label, 2.0" X .275", 140 Per Sheet, Polyester, White, 1000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG69L-789

**Type** TAG69L

**Color** White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
  - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - LaserTags are printable using toner for long term UV exposure.
  - LaserTags come in a variety of label sizes and types to fit most applications.

**Product Description** LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

**Short Description** Laser Tag Label, 2.0" X .275", 140 Per Sheet, Polyester, White, 1000/pkg

### Product Dimensions

**Length L (Imperial)** 0.275 "

**Length L (Metric)** 6.98 mm

**Width W (Imperial)** 2.0 "

**Width W (Metric)** 50.8 mm

**Height H (Imperial)** 0.275 "

**Height H (Metric)** 6.98 mm

**Height of printable area (imperial)** 0.275 "

**Height of printable area (metric)** 6.98 mm

**Horizontal Repeat HR (imperial)** 2.000 "

**Horizontal Repeat HR (metric)** 50.80 mm

**Print Method** Laser

**Thickness T (Metric)** 64.0 µm

**Vertical Repeat VR (metric)** 6.98 mm

**Vertical Repeat VR (imperial)** 0.275 "

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 5000

**Package Quantity (Metric)** 1000

**Carton Quantity** 5000

Labels per Column 35

Labels per Row 4

Labels per Sheet 140

## Material and Specifications

---

**Material** Type 789, Polyethylenterephthalat (PET)

**Material Shortcut** 789

**Adhesive Shortcut** Acrylic

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes