




TCWM8



Article Number: 598-00267

Handi-Pak, 6 Markers Each of 1-15, 16-90 A-Z+, -, /, White, 1/pkg

 RoHS

 Download spec sheet

Base Data

Local Order Number	TCWM8
Type	TCWM8
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none">• Handi-Paks booklets fit in a pocket for easy transport and access.• A single marker can be removed at the top of each label so that the terminal block can be marked and the remaining label can be used to mark the associated wire connected to the terminal.• Markers are kitted on each page so that any marker can be removed without affecting the other markers on the page.• Markers have a micro-perforation in the middle of each marker so that they can be broken into two pieces for use on small gauge wires, eliminating waste and reducing costs.
Product Description	Handi-Paks are convenient pocket sized books that contain pages of black, pre-printed legends on a white background. The legends are printed on a plastic coated cloth label that remains flexible for use in identifying wires and cables. A strong adhesive assures long lasting identification on small wires, cables or anything requiring permanent or temporary identification.
Short Description	Handi-Pak, 6 Markers Each of 1-15, 16-90 A-Z+, -, /, White, 1/pkg

Product Dimensions

Length L (Imperial)	1.625 "
Length L (Metric)	41.27 mm
Width W (Imperial)	0.25 "
Width W (Metric)	6.35 mm
Height H (Imperial)	1.625 "
Height H (Metric)	41.27 mm
Outside Diameter Min. (Imperial)	0.1 "
Outside Diameter Min. (Metric)	2.54 mm
Outside Diameter Max. (Imperial)	0.375 "
Outside Diameter Max. (Metric)	9.52 mm

Logistics and Packaging

Quantity Per	book
Package Quantity	1
Package Quantity (Metric)	1
Labels per Column	3
Labels per Row	15
Labels per Sheet	45

Material and Specifications

Material	Vinyl Cloth (TYHC)
Material Shortcut	TYHC
Adhesive Shortcut	Acrylic
Adhesive	Rubber
Adhesive Operating Temperature	-40°F to +248°F (-40°C to +120°C)
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes