HellermannTyton

TSRP1W-29-1	
	Article Number: 250-61294 External Corner, 3/4", 1" Bend Radius, PVC, White, 10/bag
HellermannTyton ²	Rohs
Download drawing	ad spec sheet
Base Data	
Local Order Numbe	r TSRP1W-29-1
Тур	e TSRP1-29-1
Cold	or White (WH)
Features and Benefit	 Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables. An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration.
	 Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Product Descriptio	n HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems.
Short Descriptio	n External Corner, 3/4", 1" Bend Radius, PVC, White, 10/bag
Product Dimonsions	

Product Dimensions

Logistics and Packaging	
Quantity Per	EA
Package Quantity	10
Package Quantity (Metric)	10
Carton Quantity	150

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
ROHS Compliant	Yes
UL Listed (US and Canada)	No
UL Listed (US)	No

© HellermannTyton 2015