

TSRP2I-50

Article Number: 250-62501

Ceiling Drop, 1-1/4", PVC, Ivory, 10/bag



Download drawing



Download spec sheet

Base Data

Local Order Number TSRP2I-50

Type TSRP2-50

Color Ivory (IV)

Features and Benefits

- Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables.
- An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration.
- Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

Product Description HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems.

Short Description Ceiling Drop, 1-1/4", PVC, Ivory, 10/bag

Product Dimensions

Logistics and Packaging

Quantity Per EA

Package Quantity 10

Package Quantity (Metric) 10

Carton Quantity 150

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Listed (US) Yes