HellermannTyton

TSRP2I-8A



Article Number: 250-62801

One Piece Low Voltage Raceway, 1-1/4", 8.0 ft Long, PVC, Ivory, 160ft/Carton

RoHS



Base Data

Local Order Number TSRP2I-8A

Type TSRP2-8A

Color Ivory (IV)

Features and Benefits • Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to

· An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or

discoloration.

• Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93

Standards, to insure compliance with local building codes.

Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

Product Description HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent

data transmission performance of Category 6A, 6 and 5e communications systems.

Short Description One Piece Low Voltage Raceway, 1-1/4", 8.0 ft Long, PVC, Ivory, 160ft/Carton

Product Dimensions

Length L (Imperial) 8.0 ft

Length L (Metric) 2.44 m

Width W (Imperial) 1.25 "

Width W (Metric) 31.75 mm

Height H (Imperial) 0.75 "

Height H (Metric) 19.05 mm

Logistics and Packaging

Quantity Per carton

Package Quantity 160.0 ft

Package Quantity (Metric) 48.8 m

Carton Quantity 160.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Listed (US) Yes

© HellermannTyton 2015