HellermannTyton

TSRP2W-12		
	rticle Number: 250-62122	
	Reducer, 1-3/4" to 3/4" (TSRP3 to TSRP1), PVC, White, 10/bag	
HellermannTyton	Rohs	
Download drawing	ad spec sheet	
Base Data		
Local Order Numbe	r TSRP2W-12	
Тур	e TSRP2-12	
Colo	or White (WH)	
Features and Benefit	 Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access t power cables. An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration. Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards. 	
Product Descriptio	n HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems.	
Short Descriptio	n Reducer, 1-3/4" to 3/4" (TSRP3 to TSRP1), PVC, White, 10/bag	
Product Dimensions		

Logistics and Packaging

• • • •	
Quantity Per	EA
Package Quantity	10
Package Quantity (Metric)	10
Carton Quantity	600

Material and Specifications

Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
ROHS Compliant	Yes
UL Listed (US)	Yes
UL Listed (US and Canada)	No

© HellermannTyton 2015