

TSRP3FW-12

Article Number: 250-63120

Reducer 1-1/4" to 3/4" (TSRP2 to TSRP1), PVC, Office White, 10/bag



Download spec sheet

Base Data

Local Order Number TSRP3FW-12

Type TSRP3-12

Color Office White (OEWH)

Features and Benefits

- Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables.
- An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration.
- Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.

Product Description HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems.

Short Description Reducer 1-1/4" to 3/4" (TSRP2 to TSRP1), PVC, Office White, 10/bag

Product Dimensions

Logistics and Packaging

Quantity Per EA

Package Quantity 10

Package Quantity (Metric) 10

Carton Quantity 1000

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

ROHS Compliant Yes

UL Listed (US) No

UL Listed (US and Canada) No