HellermannTyton

WC2-7

Cli	iicle Number: 560-10133 p Tag, WC2, .055"071", Disply "7", White, PA66, 300/pkg RoHS
Download drawing	spec sheet
Base Data	
Local Order Number	WC2-7
Туре	WC2
Color	White (WH)
Features and Benefits	 Clip-Tags are designed to mark pre-terminated wires, pre-installed wires and wires connected to terminal blocks. Markers are open on one side so that they can be attached direct to cable.

Product Description Clip-Tags are snap-on markers which slip easily on wire and cable. The markers are non-adhesive and come on a plastic wand for trouble free installation. Clip-Tags are applied by placing the flared end of the wand over the wire, then pushing the marker over the flare to the wire. The interlocking design of these markers help to keep them aligned and readable. Clip-Tags are used on pre-terminated wires, pre-installed wires, and terminal blocks. They work well for electrical installations and in panel and wire harness shops. Each legend is printed black on a white background. Each wand contains 30 markers and each package contains 10 wands.

Short Description Clip Tag, WC2, .055"-.071", Disply "7", White, PA66, 300/pkg

Product Dimensions

Length L (Imperial)	0.091 "
Length L (Metric)	2.33 mm
Outside Diameter Min. (Imperial)	0.055 "
Outside Diameter Min. (Metric)	1.4 mm
Outside Diameter Max. (Imperial)	0.071 "
Outside Diameter Max. (Metric)	1.8 mm

Logistics and Packaging

Quantity Per	pack
Package Quantity	300
Package Quantity (Metric)	300
Carton Quantity	300

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes