## HellermannTyton

| WC6-9                            |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ar                               | ticle Number: 560-10335                                                                                                                                                                                                                                                                                                                                                                                                         |
| Cli                              | p-Tag marked 9, .106"138", Nylon, White, 300/Pkg                                                                                                                                                                                                                                                                                                                                                                                |
| HellermannTyton                  | RoHS                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Download drawing                 | spec sheet                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Base Data                        |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Local Order Number               | WC6-9                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Туре                             | WC6                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Color                            | White (WH)                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Features and Benefits            | <ul> <li>Clip-Tags are snap-on markers which slip easily on wire and cable.</li> <li>Markers are non-adhesive and come on a plastic wand for trouble free installation.</li> <li>Interlocking design of these markers help to keep them aligned and readable.</li> <li>Clip-Tags have an opening on one end which means that they can be used on pre-terminated and pre-installed wires attached to terminal blocks.</li> </ul> |
| Product Description              | ClipTags are "open" markers that has an open end which can be snapped over pre-terminated cables. Each legend i printed black on white and has a very low profile when applied to wire and cable. Available in printed legends 0 to 9, and -, each package contains 300 pieces.                                                                                                                                                 |
| Short Description                | Clip-Tag marked 9, .106"138", Nylon, White, 300/Pkg                                                                                                                                                                                                                                                                                                                                                                             |
| Product Dimensions               |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Length L (Imperial)              | 0.127 "                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Length L (Metric)                | 3.25 mm                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Outside Diameter Min. (Imperial) | 0.102 "                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Outside Diameter Min. (Metric)   | 2.6 mm                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Outside Diameter Max. (Imperial) | 0.138 "                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Outside Diameter Max. (Metric)   | 3.50 mm                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Logistics and Packaging          |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Quantity Per                     | pack                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Package Quantity                 | 300                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Package Quantity (Metric)        | 300                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Carton Quantity                  | 300                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Material and Specifications      |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Material                         | Polyamide 6.6 (PA66)                                                                                                                                                                                                                                                                                                                                                                                                            |
| Material Shortcut                |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Operating Temperature            | -40°F to +185°F (-40°C to +85°C)                                                                                                                                                                                                                                                                                                                                                                                                |
| ROHS Compliant                   |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| -                                |                                                                                                                                                                                                                                                                                                                                                                                                                                 |