

WMT8

Article Number: 598-00338

Wire Marker Tape #1, .25" X 1.25", #8, White, 1/pkg



Download spec sheet

Base Data

Local Order Number WMT8

Type WMT

Color White (WH)

- Features and Benefits**
- Dispenser protects unused markers until needed.
 - Each marker is pre-cut for easy dispense and removal.
 - Markers are coated to protect the printed text from chemicals and abrasion.
 - Dispenser is refillable making it a cost effective and efficient marking system.

Product Description The Wire Marker Tape dispenser is a plastic label dispensing container that provides a convenient, economical system for wire marking. HellermannTyton's wire marker tape features sharp, crisp, pre-printed legends where are coated to resist smearing and abrasion. Each marker is provided on a carrier strip that prevents adhesive contamination prior to installation, assuring permanent, non-flagging marker ends.

Short Description Wire Marker Tape #1, .25" X 1.25", #8, White, 1/pkg

Product Dimensions

Length L (Imperial) 1.25 "

Length L (Metric) 31.75 mm

Cable Diameter Min. (Metric) 0.00 mm

Width W (Imperial) 0.25 "

Width W (Metric) 6.35 mm

Height H (Imperial) 1.25 "

Height H (Metric) 31.75 mm

Bundle Diameter Min. (Imperial) 0.1 "

Bundle Diameter Min. (Metric) 2.54 mm

Bundle Diameter Max. (Imperial) 0.375 "

Bundle Diameter Max. (Metric) 9.52 mm

Outside Diameter Min. (Imperial) 0.1 "

Outside Diameter Min. (Metric) 2.54 mm

Outside Diameter Max. (Imperial) 0.375 "

Outside Diameter Max. (Metric) 9.52 mm

Logistics and Packaging

Quantity Per box

Package Quantity 1

Package Quantity (Metric) 1

Carton Quantity 1

Material and Specifications

Material Tyvek

Material Shortcut Tyvek

Adhesive Acrylic

Adhesive Shortcut Acrylic

Adhesive Operating Temperature -40°F to +248°F (-40°C to +120°C)

Operating Temperature -40°F to +248°F (-40°C to +120°C)

ROHS Compliant Yes