




SW2015




Revision level			Revision Record	Changed	Date	Approved	Date
Drawing	State	Part					
01.1	Design Release		SEE ECN# 013740	CAS	2/21/2018	KAC	2/21/2018




M




N




O




P




Q




R




S




T



U



V



W



GLOBAL PART NAME	TYPE	DRAWING REFERENCE	WIDTH	HEIGHT	LABELS PER ROW	LABELS PER COLUMN	LABELS PER SHEET	PACKAGE QUANTITY
TAG11L-789-WH	TAG11L-789	M	.65	.20	10	48	480	5000
TAG13L-789-WH	TAG13L-789	N	.75	.25	8	39	312	5000
TAG14L-789-WH	TAG14L-789	O	1.0	.375	7	25	175	5000
TAG15L-789-WH	TAG15L-789	P	1.0	.50	7	19	133	5000
TAG96L-789-WH	TAG96L-789	Q	1.875	.25	4	36	144	1000
TAG69L-789-WH	TAG69L-789	R	2.0	.275	4	35	140	5000
TAG67L-789-WH	TAG67L-789	S	2.87	.375	2	25	50	1000
TAG66L-789-WH	TAG66L-789	T	3.59	.375	2	25	50	1000
TAG68L-789-WH	TAG68L-789	U	3.8	.275	2	35	70	2500
TAG45L-789-WH	TAG45L-789	V	4.0	.80	2	12	24	5000
TAGPHONE-PAP-BK	TAGPHONE	W	1.75	.375	4	21	84	1000

NOTES:

1. SHEET SIZE 8.5"x11"
2. TEMPERATURE RANGE: -40°F TO +300°F (-40°C TO +149°C)
3. ADHESIVE TYPE: PERMANENT PRESSURE SENSITIVE ACRYLIC
4. OUTDOOR DURABILITY: 2 YEARS
5. LINER: 90#
6. RoHS
7. 789 MATERIAL: WHITE LASER POLYESTER

Material PET	Units: inches	<p>The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.</p>	Drawn	GRW	3/2/2017	Article/Type-No	TAG_-789	Scale	
	Dimension without tolerances details to: .xxxx = ±.0005 .xxx = ±.005 .xx = ±.01 .x = ±.03 None = ±.06 ∠ = ±0.5° Dimension Formatted in [mm]		Approved	KAC	3/2/2017	Title	789 LASER TAG LABEL	Project Number	PRP 17-0709
	<p>HellermannTyton North America Email: corp@htamericas.com Web: www.hellermann.tyton.com</p>			Drawing-No	PRODUCTION : Phase		Format	AH	
				<p>17-0709-001-CSU</p>			Sheet	1/1	